



The OP24516DS antenna is an indoor/outdoor pole mounted omnidirectional antenna designed for 802.11n applications. As a 6-element MIMO antenna, each port operates over the 2.4GHz and 5 GHz bands, providing a broadband solution in a single radome. It features a low profile radome and is designed to withstand the rigors of outdoor applications with an IP67 Ingression Protection rating. The radiation patterns are uniform and symmetrical, providing high levels of signal density into defined coverage zones. This antenna greatly enhances the performance of 802.11n systems.

FEATURES AND BENEFITS

- Low profile esthetically neutral housing
- Both indoor/outdoor
- 6-element MIMO solution
- IP67 rating
- Conformance to RoHS

ELECTRICAL SPECIFICATIONS

	2400-2500	5150-5875
Operating Frequency (MHz)	2400-2500	5150-5875
Gain (dBi)	2.0 typical (2.8 max)	4.8 typical (6.5 max)
Vertical Plane 3 dB Beamwidth	66°	30°
Horizontal Plane 3 dB Beamwidth	360°	360°
Isolation Port-to-port (dB)	20	25
Number of Ports	6	
VSWR – Max	2.0:1	
Nominal Impedance (Ohms)	50	
Polarization	Linear, Vertical	
Max Power - Ambient 25°C (W)	30 (5W x 6 ports)	

MECHANICAL SPECIFICATIONS

Dimensions – diameter x height – mm (inches)	209.6 x 116.5 (8.25 x 4.59)
Weight – kg (lbs.)	1.6 (3.53)
Cable Type	Plenum rated RG58
Radome Material	Polycarbonate, white

ENVIRONMENTAL SPECIFICATIONS




Wind Survival – km/hr (mph)	200 (125)
Operating Temperature – °C (°F)	-30 to +70°C (-22 to +158°F)
Storage Temperature – °C (°F)	-40 to +85°C (-40 to +185°F)
Ingress Protection Rating	IP67

CONFIGURATION




PART NUMBER	CABLE LENGTH	CONNECTOR
OP24516DS-91NM	Six at 910 mm ±18 mm (Six at 36 in ±0.71 in)	Six, Type N
OP24516DS-91RSMM	Six at 910 mm ±18 mm (Six at 36 in ±0.71 in)	Six, Reverse Polarity SMA Male

RADIATION PATTERNS




Azimuth, 2400 MHz






Elevation, 2400 MHz



Azimuth, 5550 MHz



Elevation, 5550 MHz



Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2018 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.



Americas: +1.847.839.6925
IAS-AmericasSales@lairdtech.com
Europe: +44.1628.858941
IAS-EUSales@lairdtech.com
Asia: IAS-AsiaSales@lairdtech.com
Middle East and Africa:
+44.1628.858941
IAS-MEASales@lairdtech.com
<https://connectivity.lairdtech.com>