

Fiber Cleavers



BI-05

- Economical Price
- Compact Design

CI-01



CS-01A



CI-02

- Long life cycle with its stability by adopting double slide bearing system.
- Single action cleave system with fiber chip collector.
- Oil Damper System



CATEGORY	CI-01	CS-01A
Fiber Diameter	125μm	125μm
Coating Diameter	250 ~ 900μm	250 ~ 900μm
Cleave Angle	90°± 0.5°	90°± 0.5°
Blade Life time	50,000	50,000
Applicable Splicer	K9, K11	KF4
Cleave Length	Single 10mm ~ 16mm	Single 10mm ~ 16mm
Dimensions	58×58×50mm	58×58×50mm
Weight	244g	244g

CATEGORY	CI-02
Fiber Diameter	125μm
Coating Diameter	250 ~ 900μm
Cleave Angle	90°± 0.5°
Blade Life time	50,000
Cleave Length	Single 10mm ~ 16mm, Ribbon 10mm
Dimension	84×65×54mm
Weight	420g

CI-06



CATEGORY	CI-06
Cleave Angle	90°± 0.5°
Cleave Life	2,000
Dimension	19×32×124mm
Weight	70g

CI-08

- Typical Cleaving Angle Deviation: 6° ~ 9°
- Just one touch for tension, twisting, cleaving
- Oil Damper System



CATEGORY	CI-08
Fiber Diameter	125μm
Coating Diameter	250 ~ 900μm
Cleave Angle	6° ~ 9°
Blade Life time	Max. 30,000
Dimension	104×72×56mm
Weight	400g

ILSINTECH KOREA

#39, Techno 3-ro, Yuseong-gu, Daejeon, Korea (Zip. 305-509)

| Tel +82 42.671.5610 | Fax +82 42.671.5612

USA 4230 LBJ Freeway, Ste.149 Dallas, TX 75244 | (+1) 972 556 0916, (+1) 972 239 5836

CHINA Room 101 Li Ming Building, No111 Gui Qing Road Xuhui District, Shanghai, China | (+86) 21 5836 0950

INDIA ILSintech Trading India Pvt.Ltd 621, Devika Tower, Nehru Place New Delhi 110019 | (+91) 11 4055 5954, (+91) 11 4056 7229

RUSSIA Office 401(Kotra) 4F Hotel "Korston" 15 st. Kosygina, Moscow, Russia | (+7) 985 9111987

EUROPE Zirovnicka 2/2389 106 00 Prague 10, Prague, Czech Republic | (+420) 725 001 757

INDONESIA FACTORY Dusun 02 Blok Babakan RT01/Rw03, Desa Sukaraja Wetan, Jatiwangi, Majalengka, Jawa Barat, Indonesia

Auto Rotation Blade Cleavers



BI-07 (Rotation Blade)

- Single Action(Full Automatic) for cleaving & collecting fiber chips
- Oil Damper System
- Blade Life time 75,000

CI-03AT



CI-03RT



CS-01BT



CI-03BT



CS-03AT



CATEGORY		CI-03AT	CI-03BT	CS-03AT	CS-01BT	CI-03RT
Fiber Diameter		125μm	125μm	125μm	125μm	125μm
Coating Diameter		250 ~ 900μm	250 ~ 900μm	250 ~ 900μm	250 ~ 900μm	250 ~ 900μm
Cleave Angle		90°± 0.5°	90°± 0.5°	90°± 0.5°	90°± 0.5°	90°± 0.5°
Blade Life time		75,000	75,000	75,000	75,000	75,000
Applicable Splicer		-	-	K9, K11	KF4	KR7
Cleave Lengths	Universal Holder	Single 10mm ~ 16mm	Single 10mm ~ 16mm	Single 8mm ~ 16mm	Single 7mm ~ 16mm	X
	Exchange Holder	X	X	Single 8.0mm	Single 7.0mm	Ribbon 10mm
Dimensions		58×58×50mm	90×58×50mm	90×58×50mm	90×58×50mm	90×58×50mm
Weight		244g	276g	276g	276g	260g
Chip-Box		X	O	O	O	O

ILSINTECH KOREA

#39, Techno 3-ro, Yuseong-gu, Daejeon, Korea (Zip. 305-509)

| Tel +82 42.671.5610 | Fax +82 42.671.5612

USA 4230 LBJ Freeway, Ste.149 Dallas, TX 75244 | (+1) 972 556 0916, (+1) 972 239 5836

CHINA Room 101 Li Ming Building, No111 Gui Qing Road Xuhui District, Shanghai, China | (+86) 21 5836 0950

INDIA ILSintech Trading India Pvt.Ltd 621, Devika Tower, Nehru Place New Delhi 110019 | (+91) 11 4055 5954, (+91) 11 4056 7229

RUSSIA Office 401(Kotra) 4F Hotel "Korston" 15 st. Kosygina, Moscow, Russia | (+7) 985 9111987

EUROPE Zirovnicka 2/2389 106 00 Prague 10, Prague, Czech Repulic | (+420) 725 001 757

INDONESIA FACTORY Dusun 02 Blok Babakan RT01/Rw03, Desa Sukaraja Wetan, Jatiwangi, Majalengka, Jawa Barat, Indonesia